

## GSR2700 ISX Specifications

Positioning <sup>1</sup>		
Static <sup>2</sup>	H: 3.0 mm + 0.5 ppm V: 10.0 mm + 1.0 ppm	
Rapid Static <sup>3</sup>	H: 5.0 mm + 1.0 ppm V: 10.0 mm + 1.0 ppm	
Kinematic, Stop-and-Go <sup>4</sup>	H: 10.0 mm + 1.0 ppm V: 20.0 mm + 1.0 ppm	
RTK <sup>5</sup>	H: 10.0 mm + 1.0 ppm V: 20.0 mm + 1.0 ppm	
DGPS <sup>6</sup>	25 cm RMS	
Stand-alone Position	1.5 m CEP Horizontal	
Latency	0.02 sec (typical)	
RTK Initialization <sup>5</sup>	3-10 sec (typical) based on satellite constellation and baseline length.	
Tracking Capability		
Channels	72 universal channels: 14 L1, 14 L2, 6 L5 GPS 12 L1, 12 L2 GLONASS 2 SBAS	
Time to First Fix- Cold Start	50 sec	
Warm Start	40 sec	
Hot Start	30 sec	
Signal Reacquisition	0.5 sec L1, 1.0 sec L2	
Receiver Technology	Pulse Aperture Correlator (PAC)	
Physical		
Enclosure	Magnesium alloy housing	
Weight (no internal radio)	1.6 kg	3.5 lb
Weight (with internal radio)	1.8 kg	3.9 lb
Size L x W	22.5 cm x 10.5 cm 8.9 in x 4.1 in	
Power Requirements		
Batteries	Internal batteries standard, external batteries available	
Consumption	< 5 W using internal radio	
Power Input	+9 VDC to +18 VDC	
Operating Time – RTK Base	9 hours	
Operating Time – RTK Rover	10 hours	
Operating Time – Static/DGPS	16 hours	

Environmental		
Operating Temperature	-40°C to +65°C	-40°F to +149°F
Storage Temperature	-40°C to +85°C	-40°F to +185°F
Humidity	100% condensing	
Dust and Waterproof	Complete protection against dust ingress. Protected against immersion up to 1.0 m (IPX7).	
Shock <sup>8</sup>	2.0 m pole drop	
Ports		
Communication	2 x RS232, 1 x USB, 2 x Bluetooth	
Power	1 x power	
Interface		
Operation	Single-button operation for power, receiver reset and file management	
Display	LED display status indicators	
Status Indicators	Power, battery life, satellites tracked, available memory, occupation timer, communications status	
Audible Indicators <sup>7</sup>	Audible notifications for receiver status information; available in a variety of languages	
Data Recording and Message Formats		
Memory	64 MB standard, upgradeable to 2 GB	
Memory Life	500 hours at 10 second interval (6 SV)	
Standard Input/Output	RTCM, RTCM V3.0, RTCM, CMR, CMR+, NTRIP, NMEA-0183 out, PPS out, Mark in	
Data Rate	20 Hz	
Data Links		
Internal UHF	380-470 MHz (Tx/Rx) Selectable 10 mW to 1 W	
Internal GSM/GPRS	850/1800 MHz or 900/1900 MHz band	
External UHF <sup>9</sup>	Yes. Fully supported.	
Antenna		
Type	Internal Pinwheel™ GNSS antenna	

1. Accuracy depends on the number of satellites used, obstructions, satellite geometry (DOP), occupation time, multipath effects, atmospheric conditions, baseline length, survey procedures and data quality.  
 2. 90% confidence level.  
 3. 1 sigma.  
 4. With a suitable reference station. DGPS support includes WAAS and EGNOS.  
 5. RTK initialization time based on unobstructed observing conditions, 7 satellites and a baseline length of less than 20km.  
 6. Shock specifications based on receiver without cables attached.  
 7. English, Spanish, Japanese, French, Chinese, Russian, Italian, Portuguese, Korean, General Tones.  
 8. Supports most external data links with serial connection, such as Pacific Crest and SATEL UHF radios, and select Bluetooth devices, such as Bluetooth-enabled mobile phones.

SOKKIA

GSR2700 ISX



Fully Integrated High-Performance GNSS System

## SOKKIA Worldwide

SOKKIA CO., LTD. Head Office, Japan Phone +81-46-248-7964 www.sokkia.co.jp ISO9001 Certified UQA-0557

SOKKIA CORPORATION Head Office U.S.A. Phone +1-800-255-3813 www.sokkia.com

SOKKIA CORPORATION Head Office Canada Phone +1-905-239-5810 www.sokkiacanada.com

SOKKIA LATIN AMERICA Head Office Latin America Phone +1-305-599-4701 www.sokkialatinamerica.com

SOKKIA PTY. LTD. Head Office Australia, New Zealand and South Pacific Phone +61-2-9638-3400 www.sokkia.com.au

SOKKIA BV Head Office Europe &amp; other CE countries Phone +31-9036-649600 www.sokkia.net

SOKKIA KOREA CO., LTD. Head Office Republic of Korea Phone +82-2-934-0491 www.sokkia.co.kr

SOKKIA SURVEYING INSTRUMENTS TRADING (SHANGHAI) CO., LTD. Shanghai Office, People's Republic of China Phone +86-21-62541844 www.sokkia.com.cn

SOKKIA CO., LTD. Beijing Representative Office, People's Republic of China Phone +86-10-65660066 www.sokkia.com.cn

POINT, Inc. – Integrated Measurement Solutions

©2027 POINT, Inc. SOKKIA is a trademark of SOKKIA Co. Ltd. All rights reserved. Microsoft Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by SOKKIA is under license. Advance is a trademark of NovAtel, Inc., registered with the U.S. Patent and Trademark Office and in other countries. Other trademarks and trade names are those of their respective owners.

SOKKIA

790-0-0064  
Printed in the U.S.A. – 5/07

HERITAGE | QUALITY | SUPPORT | VALUE

# GSR2700 ISX

## Fully Integrated High-Performance GNSS System

The GSR2700 ISX is an advanced GNSS (Global Navigation Satellite System) receiver from SOKKIA that delivers it all. Multi-frequency GPS + Russian-based GLONASS satellite tracking capability. Long-range RTK positioning. Seamless Virtual Reference Station support. Multiple Bluetooth® connections for cable-free surveying convenience. And it is the first and only receiver of its kind to offer voice messages for audible status notification in the field. We think you will agree – the GSR2700 ISX is absolutely our best GPS system yet.



## GPS + GLONASS

## Our best GPS system yet? Безумно! (Absolutely!)



### GSR2700 ISX Features

#### Fully integrated, rugged design.

- High-performance, multi-frequency GNSS receiver and antenna, Bluetooth wireless technology, memory, batteries and internal data link in one compact enclosure



#### GPS + GLONASS satellite tracking capability.

- 72 universal GNSS channels support all GPS and GLONASS signals
- Better satellite coverage means increased efficiency on the job
- Improved positioning in urban areas and in areas with dense tree coverage
- SBAS tracking – standard



#### AdVance™ RTK.

- Initializes within seconds for consistent centimeter-level positioning
- Extended baseline range of 40 km or more with superior accuracy and reliability
- Delivers significant performance in the most challenging environments, including urban areas and areas with dense tree foliage.



#### Equipped for GPS modernization.

- Supports GPS L2C and L5 and GLONASS L1/L2 signals

#### Seamless Virtual Reference Station support.

- Compatible with Virtual Reference Station, FKP and Master Auxiliary reference networks
- Supports GSM dial-up connections and NTRIP GPRS connections
- Allows stand-alone RTK rover positioning – no base required



#### Easy “One Button” base setup.

- Simply mount the receiver on a tripod, press the power button, and begin transmitting RTK base corrections and collecting raw data in seconds
- No cables, external data link or data collector required



#### Convenient rover setup.

- Quick and easy setup requires only a range pole, data collector with bracket and the GSR2700 ISX receiver – no cables necessary!

#### Multiple Bluetooth connectivity.

- Connect to multiple Bluetooth wireless peripherals for cable-free convenience, outstanding range and unmatched reliability

#### Voice messages.

- The only receiver of its kind to provide audible status notification in the field
- Available in English, French, Spanish, Japanese, Italian, Russian, Portuguese, Korean, Chinese and generic tones

#### Superior LED display panel.

- Easy-to-read, informative LED display panel provides all the information you need to complete the job quickly and accurately
- Provides status indicators for satellite tracking, battery life, remaining memory, occupation time and communications

#### Environmentally sound.

- The first GNSS receiver to offer complete compliance with the European Union's RoHS lead-free directive

### The GSR2700 ISX System

- Multi-frequency GNSS receiver and antenna, Bluetooth wireless technology, memory, batteries and internal data link in one compact enclosure
- Allegro CX™ data collection hardware
- SDR+ data collection software
- Spectrum Survey Suite post-processing software
- Rugged, field-ready carrying case

### Data Collection

#### SDR+ data collection software.

- Use SDR+ data collection software and Allegro CX™ with SOKKIA GPS instruments, conventional and motorized Total Stations all on the same job
- Easy-to use, icon-based interface
- Customize the screen to display your most commonly used functions
  - Standard Windows® pull down menus for ease of use with minimal training required
  - Fully live editable database
  - Swap between coordinate systems with the push of a button
  - Perform surveys in one coordinate system and download in any other system as required, including local systems
  - Edit errors in the field, such as Target or Antenna height errors, “on the go” and get immediate recalculation of coordinates – no need to edit after the survey
  - Use control points from any coordinate system – transformation into your current coordinate system is instantaneous
  - When working on the edge of a zone, download data in both zones as required
  - Perform ETS surveys and assign/change backsights at your convenience



### The SOKKIA Difference

SOKKIA has been developing advanced products for surveying professionals around the world since 1920. We are very proud of our **heritage**. It is our mission to provide you with products of the highest **quality** so you can do the job right the first time – every time. And we **support** our products long after the sale is complete. With that kind of **value**, it is no wonder surveyors everywhere count on SOKKIA for their most important projects.



(Tribrach and tribrach adapter included with base kit only.)

#### Ready for Galileo.

Our technology partner is on the cutting edge of GNSS technology. They are also the first non-European company to be accepted as a Full Member of Galileo Services.

When Galileo is ready, SOKKIA will be too.

